

MORBARK® BEEVER™ M20R WITH INFEEED BED



BENEFITS

- Ideal for entry-level biomass production, lot and land clearing contractors, contractors and large tree services, this high-capacity, high-production chipper has more standard features than any other chipper in its class and is offered in a variety of configurations for incredible versatility.
- The powerful TorqMax™ Plus dual feed wheel compression system generates more than 10,000 lb./ft. of material pulling force.
- The 36" diameter Vortex patented chambered air impeller system increases chip throwing velocity and aids in discharging light, leafy material.
- Variable Force™ Hydraulic Down Pressure System creates 450 lbs. of perpetual down pressure.
- Like all Morbark equipment, the M20R is a long-lasting, durable machine backed by a world-class parts and service support team.



Infeed Bed

5' live rigid infeed deck with rear support drop legs and two strands of WDH-110 welded flight chain to assist in carrying material to the feed system.



Drum

The 37 3/8" diameter x 28 1/2" wide, six-knife staggered-pocket cutting system with patented removable knife holders increases chipping capacity.



Pivot Assembly

Bearing-style pivot assembly contours the radius of the drum, increases down pressure efficiency and reduces feed wheel dead space.



Reversing Auto-feed

The reversing auto-feed system with Auto Sense™ controller briefly backs material away from the drum for reduced wear and optimum engine performance while chipping.

SPECIFICATIONS

SPECIFICATIONS MAY VARY WITH EQUIPMENT OPTIONS 5/14/12

General

Chipping capacity 20"
 Height 11'10"
 Width 7'9"
 Length 24'9"
 Gross weight 16,800 lbs.
 Suspension (2) 10,000 lb. torsion
 Infeed opening 65" wide x 43" high
 Throat opening 28 1/2" wide x 22" high
 Drum 29 1/8" wide x 37 3/8" diameter
 Engine CAT, Cummins or John Deere
 Horsepower 250–365 HP
 Fuel capacity 58 gallons
 Hydraulic capacity 43 gallons
 Frame 2" x 8" tubular
 Tires (4) 235/75x17 1/2"
 Hitch 3" Pintle

Equipment Highlights

Wireless Remote Control operation with tethered back-up system controls the feed functions, yoke functions, throttle functions, rear stabilizers and hydraulic swivel discharge
 TorqMax Plus top feed wheel compression system, hydraulic lift assist, Variable Force constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and sprocket driven bottom feed wheel
 360° height-adjustable, hydraulic swivel discharge chute with chip deflectors
 Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
 Discharge clean-out door on bottom
 Hydraulic front and dual rear stabilizers

Additional Features

Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high-gloss finish, built-in UV protection, chip and chemical resistance and corrosion protection

Options

Variable speed flow control
 Turnbuckle for discharge height adjustment
 Skidder attachment mounted on drawbar
 Spark arrestor muffler
 Spare tire and rim
 Chocks and chock holders (complete set)
 Custom paint and logo packages
 Knife saver tool
 Engine stop on infeed
 Material pushing tool
 Spanish and English safety decals



MORBARK®
 BUILDING EQUIPMENT THAT CREATES OPPORTUNITIES

800.831.0042
 989.866.2381
 www.morbark.com

PO Box 1000
 8507 S. Winn Rd.
 Winn, MI 48896